

PRODUCT DATA SHEET


Drip bead for thermal insulation plaster

40 mm

Item no. 1264



Status: 01.08.2026 | 08:32



Designation	Drip bead for thermal insulation plaster 40 mm
Description	PROTEKTOR edge, base and cut-off profile made of galvanised steel with PVC coating for the precise demarcation of insulated plaster surfaces. Drip beads for creating horizontal connections with an angle of 110° for a reliable drip edge.
Product area	Exterior plaster Thermal insulation
Product category	Base profiles Profiles for insulating plaster
Types of mortar	Silicate plaster, Insulating plaster, Deposits cleaning, Gypsum mortars and mortars containing gypsum, Gypsum plaster, Lime plaster, Lime cement plaster
Plaster thickness	40 mm
Standard EN	EN 13658-2
Angular Position	110°
Reaction to fire (R2F)	E
Customs tariff number	72169180
Opened label	Purchase only possible as full packaging units.

Item number	Length (cm)	Plaster thickness	Material	Colour	Packaging unit
100976	300.00	40 mm	Galvanised steel, with PVC coating	10 - white	15 PCS / 54 BUN

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!