

PRODUCT DATA SHEET



Connecting profile for dry lining

12,5 mm PB

Item no. 1311



Status: 12.04.2024 | 12:04



Designation	Connecting profile for dry lining 12,5 mm PB
Description	Stop profile made of galvanised steel for assemblies underneath plasterboard panels, with a 15-mm shadow joint (closed). For creating plastered single edges at plastered junctions, e.g. sliding ceiling and wall connections, for 12.5-mm plasterboard panels.
Product area	Internal construction
Product category	Design profiles
Plaster thickness	1 mm
Material	Galvanised steel
GK/Plate	12,5 mm
Standard EN	EN 14353
Standard	EN 13658-1
Product length	300 cm
Reaction to fire (R2F)	A1
Packaging Unit	15 PCS / 108 BUN
Shadow gap	15 mm

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!