

PRODUCT DATA SHEET

Plaster primer economy

20 kg

Item no. 14443



Status: 10.09.2026 | 09:37



Designation	Plaster primer economy 20 kg
Description	PROTEKTOR Plaster Base economy is a white pigmented, well-covering, non-slip, universal primer for textured plasters in interior and exterior areas. Water-dilutable, water-repellent, alkali-resistant, good covering capacity, high adhesive strength, ready to use.
Product area	Interior plaster Wet rooms Interior finishing Exterior plaster
Product category	Construction chemistry
Application Areas	PROTEKTOR plaster base economy is used as a primer and bonding agent prior to final coatings on mineral substrates with mineral plasters, silicate, silicone resin or dispersion plasters. PROTRKTOR-Putzgrund economy reduces or equalises the absorbency of the plaster substrate, improves the bond and makes it much easier to apply and structure the top coats. PROTEKTOR-Putzgrund economy is not suitable for horizontal surfaces exposed to standing water.
Appearance	White, matt.
Materialbase	synthetic resin dispersion
Density	1,55 g/cm ³
Underground	The substrate must be clean, dry, grease-free and sound. Old coatings that do not adhere reliably must be removed. Sanding or chalking substrates must be pre-treated with suitable unpigmented primers, such as PROTEKTOR-Tiefengrund LF economy. Suitable substrates are gypsum, lime, lime-cement and cement-based plasters without paint, provided they are clean and dry. Observe VOB, Part C, DIN 18363.
Treatment	PROTEKTOR-Putzgrund economy should be stirred undiluted with a slow-running mixer before use and then diluted with water to a maximum of 10% depending on the absorbency of the substrate. For subsequent coloured plaster coatings, colour the plaster base in the approximate colour of the final coat using standard full-tone, tinting colours or tinting concentrates. Apply with a brush or lambskin roller.
Consumption	Approx. 200–350 g/m ² depending on the substrate.
Tool Cleaning	Tools such as brushes, ceiling brushes, etc. must be cleaned with water immediately after use, otherwise they will stick together.
Drying time	Surface dry and ready for plastering after 12 hours at +20°C and 65% relative humidity. Please note that drying may be delayed at cool temperatures and/or high humidity.
Treatment Temperature	Not below +5°C (air and building material temperature).
Overplastering Ability	EU limit value for this product (Cat. A/h): 30 g/l (2010). This product contains < 10 g/l VOC.
Storage	Cool, dry, frost-free. Unopened containers can be stored for 12 months. Keep opened containers tightly closed and use soon.

PRODUCT DATA SHEET

Plaster primer economy

20 kg

Item no. 14443



Disposal	In accordance with official regulations. Only completely empty containers should be recycled. AVV waste code no. 080112.
Content Declaration	Acrylic resin dispersion, titanium dioxide, calcium carbonate, quartz powder, water, film-forming aids, additives. Contains 1,2-benzisothiazol-3(2H)-one; mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause allergic reactions.
Further technical feature	Information on the VOC Directive: EU limit value for the product (Cat. A/h): 30 g/l (2010) This product contains < 5 g/l VOC. Product code according to GISBAU (GISCODE): Pigmented, water-dilutable primers Product code: BSW 20
Security Advice	The usual protective measures must also be observed when processing low-pollutant primers. We recommend not inhaling spray mist. Keep product out of reach of children. Do not allow to enter drains, waterways or soil. Observe the information in the safety data sheet!
Annotation	EU limit value for this product (Cat. A/h): 30 g/l (2010). This product contains < 10 g/l VOC.
Customs tariff number	32149000
Opened label	Purchase only possible in full pallets.

Item number	Length (cm)	Packaging unit
119947	0.00	1 PCE / 32 BUC

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!