

PRODUCT DATA SHEET

Composite bead TILE-TAPE for corners in wet areas
role
Item no. 37348



Status: 02.08.2026 | 16:57



Designation	Composite bead TILE-TAPE for corners in wet areas role
Description	The flexible paper-flocked PROTEKTOR composite profile from the roll, for use under tiles and slabs, prevents leaks caused by cracking on internal, external and angled edges. Tile-Tape has a higher tear resistance than paper or fabric tapes, as well as mould-resistant properties. Particularly suitable for wet areas (baths, showers, tiled worktops, etc.) on fibre cement boards, GK boards, etc.
Product area	Interior finishing
Product category	Composite profiles
Plaster thickness	1 mm
Material thickness	0,8 mm
Product width	57 mm
Revision	Smooth the surface of the composite. Once the levelling compound has dried, a further coat can be applied if required.
Leg length	28,5 mm
Application Areas	For use under tiles and slabs, to prevent leaks caused by cracking on internal, external and angled edges. Particularly suitable for wet areas (baths, showers, tiled worktops, etc.) on fibre cement boards, GRP boards, etc.
Underground	The substrate must be stable, solid, clean and dry.
Treatment	1. Cut the strips to size, cut off the corners at a 45° angle. For inside or outside corners, fold at the centre crease to the desired angle. 2. Apply the appropriate levelling compound to the substrate and apply the strip. On inner edges with the printed side facing outwards, on outer edges with the printed side facing the wall. 3. Align by hand using even pressure. 4. Remove the excess material with a spatula and fill in the strips evenly. Once the levelling compound has dried, the edge can be sanded. 5. The processing of the composite is now complete. Depending on the further surface coating, tile adhesive, for example, can now be applied with a notched trowel and tiles or boards embedded.
Consumption	Roll goods can be cut to the individual length on site, thus reducing waste and costs. The consumption of levelling compound depends on the surface structure and absorpency of the substrate as well as the properties of the levelling compound and is significantly reduced compared to conventional levelling profiles.
Tool	It can be applied with all standard drywall tools.

PRODUCT DATA SHEET

Composite bead TILE-TAPE for corners in wet areas
role
Item no. 37348



Treatment Temperature	Do not apply below +5°C air, object and drying temperature.
Overplastering Ability	Please observe the additional processing instructions and data sheets for the levelling compounds used.
Storage	Store in a cool, dry place protected from moisture.
Disposal	Offcuts of the composite strips can be disposed of with the residual waste.
Annotation	Please observe the additional processing instructions and data sheets for the levelling compounds used.
Customs tariff number	39162000
Opened label	Purchase only possible as full packaging units.

Item number	Length (cm)	Plaster thickness	Packaging unit
120425	3,050.00	1 mm	12 ROL / 24 BOX

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!