

PRODUCT DATA SHEET

Flexible corner bead for dry lining
Degree 120° to 140°
Item no. 3771



Status: 02.08.2026 | 01:45

Designation	Flexible corner bead for dry lining Degree 120° to 140°
Description	The flexible PROTEKTOR corner bead for drywall construction enables simple and clean design of external corners in an angle range between 120° and 140°, making it an indispensable solution for challenging corner configurations. The high degree of accuracy of fit facilitates installation and ensures lasting stability.
Product area	Interior finishing
Product category	Filler profiles
Plaster thickness	2 mm
head shape	Rund
Application Areas	Particularly suitable for edges on plasterboard constructions with an angle of 120° to 140°.
Underground	Suitable for drywall substrates. Ensure that the surface is clean and dust-free before installation.
Treatment	The profile must be secured with additional brackets.
Customs tariff number	39162000
Processing instructions	Secure the profile with additional clips.
Opened label	Purchase only possible as full packaging units.

Item number	Length (cm)	Plaster thickness	Material	Colour	Packaging unit
118640	305.00	2 mm	Hard PVC	10 - white	70 PCS / 80 BOX

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!