


PRODUCT DATA SHEET

U connection profile for hat ceiling profile
UD 17,2
Item no. 5167



Status: 31.07.2026 | 20:57



Designation	U connection profile for hat ceiling profile UD 17,2
Description	Application area: connection profile for hat profiles (e.g. 5114 and 50198) on hanging ceilings and wall facings.
Product area	Dry lining
Product category	Stand profiles for ceiling and wall
Material thickness	0,6 mm
Standard EN	EN 14195:2005/AC:2006
Standard	DIN18182-1
Galvanizing	tested to standard
Product width	17,2 mm
Reaction to fire (R2F)	A1
Customs tariff number	73089059
Opened label	Purchase only possible as full packaging units.

Item number	Length (cm)	Material	Packaging unit
100665	300.00	Galvanised steel	12 PCS / 50 BUN

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!