


PRODUCT DATA SHEET

C-stud
C 150-50-06
Item no. 5224



Status: 31.07.2026 | 20:43



Designation	C-stud C 150-50-06
Description	Application area: stand profile for walls/wall faces or support profile for free-spanning ceilings. H cut-out at each end, continuously every 250 mm and subsequently every 500 mm.
Product area	Dry lining Lightweight steel construction
Product category	Stand profiles for ceiling and wall Long-Span Beams – ediBeam
Material thickness	0,6 mm
Standard EN	EN 14195:2005/AC:2006
Standard	DIN18182-1
Galvanizing	tested to standard
Product width	148,8 mm
Reaction to fire (R2F)	A1
Overplastering Ability	H cut-out at each end, every 250 mm and subsequently every 500 mm
Annotation	H cut-out at each end, every 250 mm and subsequently every 500 mm
Customs tariff number	73089059
Opened label	Purchase only possible as full packaging units.

Item number	Length (cm)	Material	Packaging unit
115623	270.00	Galvanised steel	4 PCS / 12 BUN
109990	400.00	Galvanised steel	4 PCS / 12 BUN
109991	600.00	Galvanised steel	4 PCS / 12 BUN

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!