

# PRODUCT DATA SHEET


Adjusting strip for Nonius hanger acoustically insulated

590 mm

Item no. 56325



Status: 11.04.2024 | 02:04



<b>Designation</b>	Adjusting strip for Nonius hanger acoustically insulated 590 mm
<b>Description</b>	Application area: ceiling sub-constructions connected to vernier subdividers for improving wall facings.
<b>Product area</b>	Dry lining / lightweight steel construction
<b>Product category</b>	Sound Insulation silencio
<b>Material</b>	Galvanised steel
<b>Standard EN</b>	EN 13964:2014
<b>Test Standard DIN</b>	DIN 18168-2
<b>Galvanizing</b>	tested to standard
<b>Product length</b>	59 cm
<b>Capacity class</b>	k.A.
<b>Treatment</b>	- Attach the Nonius upper part at the required centre distance using suitable fasteners. - Connect the Nonius lower part with two safety clamps or a safety clip. - After aligning the substructure, secure the securing bracket by bending it over.
<b>Packaging Unit</b>	100 PC / 12 BOX
<b>Load bearing capacity</b>	NPD*
<b>Processing instructions</b>	see processing description

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!