


PRODUCT DATA SHEET

Fixing clip C3-C5M universal+
for Nonius
Item no. 58107



Status: 08.09.2026 | 12:59



Designation	Fixing clip C3-C5M universal+ for Nonius
Description	Application area: ceiling sub-constructions as a connection between vernier shells and subdividers, with increased corrosion resistance requirements. Please apply 2 pieces per connection.
Product area	Dry lining
Product category	Anti corrosion defendo
Material thickness	2,5 mm
Standard EN	EN 13964:2014
Galvanizing	tested to standard
Standard coating profile	DIN 18219:2024
Reaction to fire (R2F)	A2-s1, d0
Treatment	- 2 pieces per connection
Load bearing capacity	NPD
Customs tariff number	73089059
Processing instructions	See processing description.
Opened label	Purchase only possible as full packaging units.

Item number	Length (cm)	Material	Packaging unit
119474	0.00	Steel wire, galvanised with coating	100 PCE / 600 BOX

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!