


PRODUCT DATA SHEET

C-stud C5M universal+
C 50-06
Item no. 59211



Status: 31.07.2026 | 13:21



Designation	C-stud C5M universal+ C 50-06
Description	Application area: stand profile for walls/wall faces or support profile for free-spanning ceilings with increased corrosion resistance requirements. H cut-out at each end, continuously every 250 mm and subsequently every 500 mm.
Product area	Dry lining
Product category	Anti corrosion defendo
Material thickness	0,6 mm
Standard EN	EN 14195:2005/AC:2006
Standard	DIN18182-1
Galvanizing	tested to standard
Product width	48,8 mm
Standard coating profile	DIN 18219:2024
Reaction to fire (R2F)	A2-s1, d0
Customs tariff number	73089059
Opened label	Purchase only possible as full packaging units.

Item number	Length (cm)	Material	Packaging unit
110083	300.00	Galvanised steel with coating	8 PCS / 16 BUN
110084	400.00	Galvanised steel with coating	8 PCS / 16 BUN

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!