


PRODUCT DATA SHEET

Nonius hanger
for hanging wood
Item no. 6015



Status: 01.09.2026 | 08:32



Designation	Nonius hanger for hanging wood
Description	Application area: ceiling sub-constructions with vernier suspensions.
Product area	Dry lining
Product category	Standard accessoires
Material thickness	1,2 mm
Standard EN	EN 13964:2014
Standard	DIN18168-2
Galvanizing	tested to standard
Capacity class	0,40 kN
Reaction to fire (R2F)	A1
Treatment	- The lower part of Nonius hanger is connected to the upper part of the Nonius by means of two safety clamps or a safety clip. - Connect the lower part of the Nonius to the wooden substructure on both sides using suitable fasteners. - Readjust if necessary - After aligning the substructure, secure the safety clip by bending it over.
Load bearing capacity	0,400 kN
Customs tariff number	73089059
Processing instructions	See processing description.
Opened label	Purchase only possible as full packaging units.

Item number	Length (cm)	Material	Packaging unit
101081	19.00	Galvanised steel	100 PCE / 100 BOX

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!