


PRODUCT DATA SHEET

Quick install hanger with special tension spring
for C 60-27
Item no. 6038



Status: 01.09.2026 | 08:20



Designation	Quick install hanger with special tension spring for C 60-27
Description	For attaching CD profiles on ceiling sub-constructions with wire support. Quick assembly facilitated by lateral wire insertion.
Product area	Dry lining
Product category	Standard accessoires
Material thickness	1 mm
Standard EN	EN 13964:2014
Standard	DIN18168-2
Galvanizing	tested to standard
Product height in mm	100 mm
Capacity class	0,40 kN
Reaction to fire (R2F)	A1
Treatment	- Attach the eyelet wire at the required centre distance using suitable fasteners. - Compress the hanger spring and insert the eyelet wire sideways until it clicks into place. - Ceiling profile can be adjusted or screwed in before or after attaching to the eyelet wire. - Readjust if necessary.
Load bearing capacity	0,400 kN
Customs tariff number	73089059
Processing instructions	See processing description.
Opened label	Purchase only possible as full packaging units.

Item number	Length (cm)	Material	Packaging unit
107902	10.00	Galvanised steel	100 PCE / 45 BOX

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

PRODUCT DATA SHEET

Quick install hanger with special tension spring
for C 60-27
Item no. 6038



All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!