

# PRODUCT DATA SHEET

Quick cross-connector flat  
for C 60-27  
Item no. 6105



Status: 01.09.2026 | 08:02



|                         |                                                                                                                                                                                                                                                                                                                                        |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Designation             | Quick cross-connector flat for C 60-27                                                                                                                                                                                                                                                                                                 |
| Description             | For creating cross connections of CD profiles on hanging ceiling sub-constructions.                                                                                                                                                                                                                                                    |
| Product area            | Dry lining                                                                                                                                                                                                                                                                                                                             |
| Product category        | Standard accessoires                                                                                                                                                                                                                                                                                                                   |
| Material thickness      | 0,8 mm                                                                                                                                                                                                                                                                                                                                 |
| Standard EN             | EN 13964:2014                                                                                                                                                                                                                                                                                                                          |
| Standard                | DIN18168-2                                                                                                                                                                                                                                                                                                                             |
| Galvanizing             | tested to standard                                                                                                                                                                                                                                                                                                                     |
| Capacity class          | 0,40 kN                                                                                                                                                                                                                                                                                                                                |
| Reaction to fire (R2F)  | A1                                                                                                                                                                                                                                                                                                                                     |
| Treatment               | - Bend the side legs to the middle part by 90 degrees. - Slide in at a slight angle over the base profile and hook the lateral legs into the support profile. - To click in the legs on the other side, press on the middle section from above until you hear them snap in. - After the installation, the profiles can still be moved. |
| Load bearing capacity   | 0,400 kN                                                                                                                                                                                                                                                                                                                               |
| Customs tariff number   | 73089059                                                                                                                                                                                                                                                                                                                               |
| Processing instructions | See processing description.                                                                                                                                                                                                                                                                                                            |
| Opened label            | Purchase only possible as full packaging units.                                                                                                                                                                                                                                                                                        |

| Item number | Length (cm) | Material         | Packaging unit    |
|-------------|-------------|------------------|-------------------|
| 103182      | 0.00        | Galvanised steel | 100 PCE / 270 BOX |

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!