

PRODUCT DATA SHEET

Connector
DN 50
Item no. 81950



Status: 31.07.2026 | 05:29



Designation	Connector DN 50
Description	PROTEKTOR connector forms the lower connection of the flexible pipe bend to the downpipe system. Together with one bend, different angle positions from 0° to 22° can be created. With two bends, different angle positions from 22° to 45° can be created, with three bends, different angle positions from 45° to 67° can be created and with four bends, different angle positions from 67° to 90° can be created.
Product area	Roof drainage
Product category	Downpipes
Customs tariff number	39174000
Opened label	Purchase also possible as a single item:

Item number	Length (cm)	Material	Colour	Packaging unit
107638	6.00	PVC-U	BC - dark brown	10 PCE / 12 BAG
107637	6.00	PVC-U	BB - grey	10 PCE / 12 BAG
107636	6.00	PVC-U	BA - white	10 PCE / 12 BAG

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!