



PRODUCT DATA SHEET

Stop bead for interior and exterior plaster
from 10 mm
Item no. 9111



Status: 30.07.2026 | 20:49



Designation	Stop bead for interior and exterior plaster from 10 mm
Description	The PROTEKTOR stop bead made of aluminium with a white base coat is suitable for interior and exterior plaster from 10 mm. Stop beads made of aluminium with a base coat can be used in private domestic bathrooms, even under tiles. In commercial kitchens and other wet rooms, swimming and indoor pools, as well as when using renovation plaster, stainless steel profiles must be installed.
Product area	Interior plaster Wet rooms Exterior plaster
Product category	Plaster/render stops Wet rooms to W2-I
Types of mortar	Silicate plaster, Reinforcing plaster organ, Insulating plaster, Deposits cleaning, Gypsum mortars and mortars containing gypsum, Gypsum plaster, Lime plaster, Lime cement plaster, Clay plaster
Plaster thickness	10 mm
Standard EN	EN 13658-1
Application Areas	For wet rooms with water exposure class up to W2-I.
Reaction to fire (R2F)	E
Leaflet	* Leaflet Planning and Application of Metallic Plaster Profiles; Publisher: European Trade Association Europrofiles, www.europrofiles.com * Leaflet Planning and Application of Metallic Plaster Profiles; Publisher: European Trade Association Europrofiles, www.europrofiles.com * Leaflet Winter Construction Sites; Publisher: Bundesverband der Gipsindustrie e.V., www.gips.de
Customs tariff number	76042990
Opened label	Purchase only possible as full packaging units.

Item number	Length (cm)	Plaster thickness	Material	Colour	Packaging unit
107584	250.00	10 mm	Aluminum, with basic coating	10 - white	25 PCS / 144 BUN
108637	300.00	10 mm	Aluminum, with basic coating	10 - white	25 PCS / 144 BUN

PRODUCT DATA SHEET

Stop bead for interior and exterior plaster
from 10 mm
Item no. 9111



This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!