

DECLARATION OF PERFORMANCE H_14927_15661

Armoured mesh
6 x 8 mm, 330 g/m²
Item 14927



Declaration of performance in accordance with EU Construction Product Regulation 305/2011	
Applicable designated standard	EAD 040016-01-0404
Designation according to standard	Gewebe aus Glasfasern zur Armierung in Putzsystemen
Protektor product name	Armoured mesh
Product area	0

Identification using product data printed onto products / packaging / documents

EAD 040016-01-0404
Protektorwerk Florenz Maisch GmbH & Co. KG

Assessment and Verification of Constancy of Performance

Performance	System	Approved body	Classification report
Organischer Inhalt	2+	NB 1020 - Technical and Test Institute for Construction Prague	
Ash content	2+	NB 1020 - Technical and Test Institute for Construction Prague	
Reaction to fire (R2F)			
Tear strength Delivery condition	2+	NB 1020 - Technical and Test Institute for Construction Prague	
Rice strength after alkaline storage	2+	NB 1020 - Technical and Test Institute for Construction Prague	
Durability Storage Lye			

Performance to be declared

Essential characteristics	Performance	Designated technical standard
Organischer Inhalt	26%, ±4%	EAD 040016-01-0404
Ash content		EAD 040016-01-0404
Reaction to fire (R2F)	kA	EAD 040016-01-0404
Tear strength Delivery condition		EAD 040016-01-0404
Rice strength after alkaline storage	2340 / 2660 N/5cm	EAD 040016-01-0404
Durability Storage Lye		EAD 040016-01-0404

The manufacturer has carried out initial type testing (ITT) as required by . The product undergoes a factory production control (FPC) which complies with the requirements of EAD 040016-01-0404 - .

The performance of the product which is referred to in this performance declaration represents the performance to be declared. The manufacturer named in this declaration of performance is solely responsible for preparing this "declaration of performance".
Signed for the manufacturer and on behalf of the manufacturer by:

Dr. Christof Maisch | CEO, Managing Partner\r
Gaggenau, on 21.09.2026