

DECLARATION OF PERFORMANCE P_1004_15368

Inside corner bead for interior plaster

8 mm, angular corner

Item 1004



Declaration of performance in accordance with EU Construction Product Regulation 305/2011

Applicable designated standard	EN 14195
Designation according to standard	
Protektor product name	Inside corner bead for interior plaster
Product area	20

Identification using product data printed onto products / packaging / documents

EN 14195 Metal lath and beads - Definitions, requirements and test methods , Internal plastering

Protektorwerk Florenz Maisch GmbH & Co. KG

8000028

Assessment and Verification of Constancy of Performance

Performance	System	Approved body	Classification report
Reaction to fire (R2F)	4, Commission decision 96/603/EG		-
Yield strength			

Performance to be declared

Essential characteristics	Performance	Designated technical standard
Reaction to fire (R2F)	A1	EN 14195
Yield strength		EN 14195

The manufacturer has carried out initial type testing (ITT) as required by Metal lath and beads - Definitions, requirements and test methods , Internal plastering. The product undergoes a factory production control (FPC) which complies with the requirements of EN 14195 - Metal lath and beads - Definitions, requirements and test methods , Internal plastering.

The performance of the product which is referred to in this performance declaration represents the performance to be declared. The manufacturer named in this declaration of performance is solely responsible for preparing this "declaration of performance".

Signed for the manufacturer and on behalf of the manufacturer by:

Dr. Christof Maisch | CEO, Managing Partner\r
Gaggenau, on 04.09.2026