

DECLARATION OF PERFORMANCE

Stop profile for dry lining

12,5 mm PB

Item 1131 | No. P_5478



Declaration of performance in accordance with EU Construction Product Regulation 305/2011	
Applicable designated standard	EN 14353
Designation according to standard	
Protektor product name	Stop profile for dry lining
Product area	20

Identification using product data printed onto products / packaging / documents

EN 14353 Metal beads and geatures profiles for use with gypsum plasterboards - Definitions, requirements and test methods
Protektorwerk Florenz Maisch GmbH & Co. KG
8000028

Assessment and Verification of Constancy of Performance

Performance	System	Approved body	Classification report
Reaction to fire (R2F)	4, Kommissionsentscheid 96/603/EG		
Dangerous substances	4		

Performance to be declared

Essential characteristics	Performance	Designated technical standard
Reaction to fire (R2F)	A1	EN 14353
Yield strength	bestanden	EN 14353
Dangerous substances	NPD	EN 14353

The manufacturer has carried out initial type testing (ITT) as required by Metal beads and geatures profiles for use with gypsum plasterboards - Definitions, requirements and test methods. The product undergoes a factory production control (FPC) which complies with the requirements of EN 14353 - Metal beads and geatures profiles for use with gypsum plasterboards - Definitions, requirements and test methods.

The performance of the product which is referred to in this performance declaration represents the performance to be declared. The manufacturer named in this declaration of performance is solely responsible for preparing this "declaration of performance".
Signed for the manufacturer and on behalf of the manufacturer by:

A handwritten signature in blue ink, appearing to read "Dr. Christof Maisch".

Dr. Christof Maisch | CEO, Managing Partner
Gaggenau, on 04.07.2024