

DECLARATION OF PERFORMANCE P_11311_15322

Stop bead for dry lining

12,5 mm PB

Item 11311



Declaration of performance in accordance with EU Construction Product Regulation 305/2011

Applicable designated standard	EN 14353
Designation according to standard	Hilfsprofil aus Metall EN 14353 - Anschlagprofil - 12,5 - Z225/275 - 3000
Protektor product name	Stop bead for dry lining
Product area	20

Identification using product data printed onto products / packaging / documents

EN 14353 Metal beads and geatures profiles for use with gypsum plasterboards - Definitions, requirements and test methods
Protektorwerk Florenz Maisch GmbH & Co. KG
8000028

Assessment and Verification of Constancy of Performance

Performance	System	Approved body	Classification report
Dangerous substances	4		
Reaction to fire (R2F)	4, Commission Decision 2000/147/EG		
Yield strength			

Performance to be declared

Essential characteristics	Performance	Designated technical standard
Dangerous substances		EN 14353
Reaction to fire (R2F)	E	EN 14353
Yield strength		EN 14353

The manufacturer has carried out initial type testing (ITT) as required by Metal beads and geatures profiles for use with gypsum plasterboards - Definitions, requirements and test methods. The product undergoes a factory production control (FPC) which complies with the requirements of EN 14353 - Metal beads and geatures profiles for use with gypsum plasterboards - Definitions, requirements and test methods.

The performance of the product which is referred to in this performance declaration represents the performance to be declared. The manufacturer named in this declaration of performance is solely responsible for preparing this "declaration of performance".
Signed for the manufacturer and on behalf of the manufacturer by:

Dr. Christof Maisch | CEO, Managing Partner
Gaggenau, on 04.09.2026