

DECLARATION OF PERFORMANCE

Connecting profile for dry lining

12,5 mm PB

Item 1311 | No. P_5432



Declaration of performance in accordance with EU Construction Product Regulation 305/2011	
Applicable designated standard	EN 14353
Designation according to standard	
Protektor product name	Connecting profile for dry lining
Product area	20

Identification using product data printed onto products / packaging / documents

EN 14353 Metal lath and beads - Definitions, requirements and test methods , Internal plastering
Protektorwerk Florenz Maisch GmbH & Co. KG
8000028

Assessment and Verification of Constancy of Performance

Performance	System	Approved body	Classification report
Reaction to fire (R2F)	4, Kommissionsentscheid 96/603/EG		
Dangerous substances	4		

Performance to be declared

Essential characteristics	Performance	Designated technical standard
Reaction to fire (R2F)	A1	EN 14353
Yield strength		EN 14353
Dangerous substances	NPD	EN 14353

The manufacturer has carried out initial type testing (ITT) as required by Metal lath and beads - Definitions, requirements and test methods , Internal plastering. The product undergoes a factory production control (FPC) which complies with the requirements of EN 14353 - Metal lath and beads - Definitions, requirements and test methods , Internal plastering.

The performance of the product which is referred to in this performance declaration represents the performance to be declared. The manufacturer named in this declaration of performance is solely responsible for preparing this "declaration of performance".
Signed for the manufacturer and on behalf of the manufacturer by:

Dr. Christof Maisch | CEO, Managing Partner
Gaggenau, on 04.07.2024