

DECLARATION OF PERFORMANCE

Featured bead with shadow gap for dry lining

12,5 mm PB

Item 1371 | No. P_14634



Declaration of performance in accordance with EU Construction Product Regulation 305/2011	
Applicable designated standard	EN 14353
Designation according to standard	Hilfsprofil aus Metall EN 14353 - Anschlagprofil - 12,5 - Z275 - 3000
Protektor product name	Featured bead with shadow gap for dry lining
Product area	20

Identification using product data printed onto products / packaging / documents

EN 14353 Metal lath and beads - Definitions, requirements and test methods , Internal plastering
Protektorwerk Florenz Maisch GmbH & Co. KG
8000028

Assessment and Verification of Constancy of Performance

Performance	System	Approved body	Classification report
Dangerous substances	4		
Reaction to fire (R2F)	4, Commission decision 96/603/EG		
Yield strength	4		

Performance to be declared

Essential characteristics	Performance	Designated technical standard
Dangerous substances	NPD	EN 14353
Reaction to fire (R2F)	A1	EN 14353
Yield strength	bestanden	EN 14353

The manufacturer has carried out initial type testing (ITT) as required by Metal lath and beads - Definitions, requirements and test methods , Internal plastering. The product undergoes a factory production control (FPC) which complies with the requirements of EN 14353 - Metal lath and beads - Definitions, requirements and test methods , Internal plastering.

The performance of the product which is referred to in this performance declaration represents the performance to be declared. The manufacturer named in this declaration of performance is solely responsible for preparing this "declaration of performance".
Signed for the manufacturer and on behalf of the manufacturer by:

Dr. Christof Maisch | CEO, Managing Partner\r
Gaggenau, on 30.07.2026