

DECLARATION OF PERFORMANCE

Stop profile for interior plaster and exterior render

10 mm

Item 2180 | No. P_9466



Declaration of performance in accordance with EU Construction Product Regulation 305/2011	
Applicable designated standard	EN 13658-1
Designation according to standard	
Protektor product name	Stop profile for interior plaster and exterior render
Product area	20

Identification using product data printed onto products / packaging / documents

EN 13658-1 Metal lath and beads - Definitions, requirements and test methods , Internal plastering
Protektorwerk Florenz Maisch GmbH & Co. KG
8000028

Assessment and Verification of Constancy of Performance

Performance	System	Approved body	Classification report
Dangerous substances	4		
Reaction to fire (R2F)	4, Commission decision 96/603/EG		

Performance to be declared

Essential characteristics	Performance	Designated technical standard
Dangerous substances		EN 13658-1
Reaction to fire (R2F)	A1	EN 13658-1

The manufacturer has carried out initial type testing (ITT) as required by Metal lath and beads - Definitions, requirements and test methods , Internal plastering. The product undergoes a factory production control (FPC) which complies with the requirements of EN 13658-1 - Metal lath and beads - Definitions, requirements and test methods , Internal plastering.

The performance of the product which is referred to in this performance declaration represents the performance to be declared. The manufacturer named in this declaration of performance is solely responsible for preparing this "declaration of performance".
Signed for the manufacturer and on behalf of the manufacturer by:

Dr. Christof Maisch | CEO, Managing Partner
Gaggenau, on 23.01.2025