

# DECLARATION OF PERFORMANCE P\_9297\_14921

Stop bead for dry lining  
15 mm PB  
Item 9297



| Declaration of performance in accordance with EU Construction Product Regulation 305/2011 |                                                                     |
|-------------------------------------------------------------------------------------------|---------------------------------------------------------------------|
| Applicable designated standard                                                            | EN 14353                                                            |
| Designation according to standard                                                         | Hilfsprofil aus Metall EN 14353 - Anschlagprofil - 15,0 - Al - 2500 |
| Protektor product name                                                                    | Stop bead for dry lining                                            |
| Product area                                                                              | 20                                                                  |

Identification using product data printed onto products / packaging / documents

EN 14353 Metal beads and geatures profiles for use with gypsum plasterboards - Definitions, requirements and test methods  
Protektorwerk Florenz Maisch GmbH & Co. KG  
8000028

## Assessment and Verification of Constancy of Performance

| Performance            | System                              | Approved body | Classification report |
|------------------------|-------------------------------------|---------------|-----------------------|
| Dangerous substances   | 4                                   |               |                       |
| Reaction to fire (R2F) | 4, Commission decision<br>96/603/EG |               |                       |
| Yield strength         |                                     |               |                       |

## Performance to be declared

| Essential characteristics | Performance | Designated technical standard |
|---------------------------|-------------|-------------------------------|
| Dangerous substances      | NPD         | EN 14353                      |
| Reaction to fire (R2F)    | A1          | EN 14353                      |
| Yield strength            | bestanden   | EN 14353                      |

The manufacturer has carried out initial type testing (ITT) as required by Metal beads and geatures profiles for use with gypsum plasterboards - Definitions, requirements and test methods. The product undergoes a factory production control (FPC) which complies with the requirements of EN 14353 - Metal beads and geatures profiles for use with gypsum plasterboards - Definitions, requirements and test methods.

The performance of the product which is referred to in this performance declaration represents the performance to be declared. The manufacturer named in this declaration of performance is solely responsible for preparing this "declaration of performance".  
Signed for the manufacturer and on behalf of the manufacturer by:

Dr. Christof Maisch | CEO, Managing Partner  
Gaggenau, on 03.09.2026